

TROJAN

BATTERIE AL PIOMBO ACIDO

BATTERIE TROJAN AL PIOMBO ACIDO

CODICE TROJAN	MODELLO	L.E.U.	CAPACITÀ (Minuti)		PRESTAZIONI AVVIAMENTO		CAPACITÀ		CONFIG. STAND. TERMIN.	DIMENSIONI (mm)			Q.tà per Pallet	Peso Kg.
			@ 25 Amps	@ 75 Amps	CCA @ 0° F	CA @ 32° F	Ah/5h	Ah/20h		Larg.	Prof.	Alt.		
TRAZIONE - DEEP-CYCLE - 6 VOLT														
901262	T-105 Plus	438	447	115	-	-	185	225	HPT	264	181	284	40	28
900815	T-105	438	447	115	-	-	185	225	UT	264	181	284	40	28
901306	T-125 Plus	492	488	132	-	-	195	240	HPT	264	181	284	40	30
900822	T-125	492	488	132	-	-	195	240	UT	264	181	284	40	30
901268	T-145 Plus	673	530	145	-	-	215	260	HPT	264	181	292	40	33
900827	T-145	673	530	145	-	-	215	260	LPT	264	181	292	40	33
900931	TE-35	498	500	135	-	-	200	245	AP	244	190	276	40	31
901327	J305G	686	620	170	-	-	255	310	UT	295	178	365	18	41
901334	J305P	727	675	175	-	-	270	315	DT	295	178	365	18	43
900795	L 16G	933	750	185	-	-	305	370	UT	295	178	432	18	48
900797	L 16P	1004	805	200	-	-	320	390	DT	295	178	424	18	51
TRAZIONE - DEEP-CYCLE - 8 VOLT														
900842	T-875	438	295	117	-	-	145	170	LPT	264	181	284	40	29
900846	T-890	511	340	132	-	-	155	190	LPT	264	181	284	40	31
AVVIAMENTO - 12 VOLT														
901045	C31-1000S	-	-	-	870	1000	100	115	ST	330	173	238	45	28
901044	C31-1000A	-	-	-	870	1000	100	115	AP	330	173	238	45	28
TRAZIONE - DEEP-CYCLE - 12 VOLT														
900785	24TMX	233	140	36	440	540	70	85	UT	286	171	248	60	21
900917	27TMX	280	175	45	530	650	85	105	UT	324	171	248	45	25
900915	27TMH	326	200	51	620	760	95	115	UT	324	171	248	45	27
900889	30XHS	373	225	57	665	820	105	130	WNT	355	171	238	45	30
900920	31XHS	373	225	57	665	820	105	130	ST	330	171	241	45	30
901214	J-150	-	280	70	-	-	125	150	HPT	344	171	289	30	38
900788	J185G	727	300	85	-	-	150	180	UT	381	178	371	12	48
900848	J185P	807	375	95	-	-	160	195	DT	381	178	371	12	51



J305P



C31-1000



27TMH



J-150



T-125



24TMX