



Tipo	V <sub>N</sub> V	Capacità nominale 1,75 V/El Ah	W resi a 1,67 V/El		L mm	B mm	H Mon. mm	H Totale mm	Peso Kg	Tipo di terminale	Schema
			10 min W	15 min W							

### Vita attesa 4+5 anni

LC 2,3-12	12	2,3	10	8	177	35	61	67	0,92	Faston	+ A2 -
LC 5-12A	12	5	23	19	90	70	101	107	1,83	Faston	+ A2 -
LC 5-12B	12	5	28	23	151	53	95	101	2,28	Faston	+ A6
LC 7,2-12	12	7,2	34	27	151	65	95	101	2,5	Faston	+ A6
LC 9-12	12	9	40	30	151	65	95	101	2,75	Faston	+ A6
LC 12-12	12	12	52	42	151	98	95	101	3,85	Faston	+ A6
LC 18-12	12	18	80	61	181	77	167	167	5,7	F3	- A1 +

### Vita attesa 10 anni

LC 24-12	12	24	103	85	165	125	175	175	8,2	F6	- A1 +
LC 26-12	12	26	114	95	167	175	125	125	9	F6	- A1 +
LC 40-12	12	40	877	772	197	165	170	170	13,5	F22	- A1 +
LC 45-12	12	45	930	820	197	165	170	170	13,8	F22	- A1 +
LC 55-12	12	55	1206	1061	229	138	208	212	19,5	F15	+ A2 -
LC 65-12	12	65	1426	1254	351	167	176	176	22	F15	+ A2 -
LC 80-12	12	80	1755	1544	260	168	208	212	24	F15	+ A2 -
LC 100-12	12	100	2193	1930	330	171	214	224	32	F17	+ A2 -
LC 120-12	12	120	2632	2316	330	171	214	224	33	F17	+ A2 -
LC 135-12	12	135	2939	2586	342	172	280	285	42,5	F11	+ A2 -
LC 140-12	12	140	3000	2635	342	172	280	285	43	F17	+ A2 -
LC 150-12	12	150	3290	2895	485	172	240	240	43	F17	+ A2 -
LC 200-12	12	200	4387	3860	522	240	218	238	65,5	F17	+ A5
LC 250-12	12	250	5484	4825	496	250	218	241	78	F17	+ A5



Tipo	A	B	C	D	E
F3	12,0	∅ 5,5	5,0	11,0	2,0
F4	16,5	∅ 6,5	8,0	16,0	8,2
F5	16,5	∅ 8,0	8,5	17,0	6,0
F6	18,5	∅ 6,5	8,0	19,0	8,1
F7	26,0	∅ 8,5	11,0	23,0	8,3
F8	25,0	∅ 9,0	12,5	28,0	8,0
F9	26,0	∅ 9,0	9,0	19,0	8,3
F10	27,0	∅ 9,0	12,5	25,0	8,2
F11	24,0	∅ 10,5	11,0	25,0	8,0
F21	15,0	∅ 5,5	7,5	17,5	5,0
F22	20,0	∅ 6,5	8,0	20,0	3,0
F24	18,0	∅ 7,0	9,5	17,0	6,0
J	18,0	∅ 7,0	9,5	19,0	8,0

Tipo	A	B	C
F12	∅ 12	M5	4,0
F13	∅ 14	M6	4,0
F14	∅ 10	M5	1,5
F15	∅ 16	M6	4,0
F16	∅ 20	M6	4,0
F17	∅ 20	M8	4,0
F18	∅ 12	M6	4,0
F19	∅ 14	M5	4,0
F20	∅ 16	M5	4,0



WWW.PROCARRELL.IT